



DATASHEET  
**CY-XVT-1**



## Specifications

### Analog Tester HD y SD

**Video Format** NTSC/PAL/\*HD-CVI3.0/\*AHD3.0/\*HD-TVI3.0

**Signal Level** 1Vpp

### 12V Power Output

**Power Output** 12V/1A Output Interface : Circular outer diameter 4mm, Inner needle 1.6mm

### Audio Test

**Audio Test** A audio signal input

### Coaxial PTZ Control test

**Communication interface** Video IN BNC interface

**Communication protocols** \*CVI (dahua coax) \*AHD (Pelco c) \*TVI (Hikvision)  
\*UTC (SD-UTC)

<b>RS485 PTZ Control test</b>	
<b>Communication interface</b>	RS485
<b>Communication protocols</b>	Pelco-D/P、Samsung、Panasonic、Lilin、Yaan...more than 30 protocols
<b>Baud rate</b>	150, 300, 600, 1200, 2400, 4800, 9600, 19200bps
<b>LED torch</b>	
<b>Three LED</b>	Three 35lm LED , can tun on individually when device is off
<b>Power</b>	
<b>Charger</b>	Micro USB 5v1A charge
<b>Battery</b>	18650 lithium battery*2, capacity 2000 mAh*2, working time about 8hs
<b>System Specification</b>	
<b>Display</b>	4.3 inch TFT 480*272 resolution, 262K color, back light level adjustable
<b>Operation</b>	Power button, main control keypad of 8 keys, LED push switch *3
<b>Setting</b>	Chinese、English, user optional
<b>Keyboard tone</b>	On / Off
<b>Working environment and specification</b>	
<b>Working temperature</b>	-10°C---+55°C
<b>Working humidity</b>	30%-90%
<b>Device Dimension</b>	120*30*95mm
<b>Weight</b>	0.3kg(device with battery)

**CYGNUS**  
electronics

