

8MP RJ45 Balun

Model: BP-01PV



Introduction:

This device makes connection to a PTZ camera, hassle free. Power- Video-Audio / Data signals are all routed via UTP cable

(Cat5 or Cat6). real time HD (HD-TVI, AHD or CVI) Video can be transmitted with ease, no more special is required cabling for the data connections, simply plug in a standard cat5e or cat6 cable, and have the PTZ up and running (please note, we strongly advise the use of copper UTP cable). Used in pairs, this special set can eliminate the requirement for expensive, bulky coax cable as well as providing better interference and noise rejection.

Technical Specification:

Passive Video & Power Transceiver (Pair)
Real-Time HD transmission
60dB Crosstalk and Noise immunity
Built-in transient suppression Protection
Exceptional interference rejection
Designed specifically for CCTV camera systems
Connectors: Male BNC and RJ45 Female
Ports
Frequency Response: DC to 8MHz
Attenuation: 0.5dB
CMRR (Common Mode Rejection Ratio): 60 dB
Impedance for BNC: 75 ohms
Impedance for RJ45: 100 ohms
Working temperature: -10°C to 70°C
Storage temperature: -30°C to 70°C
Humidity: 0 to 95%
Material: ABS Plastic

Packaging Details:
Unit Type: pair Blister Packaging
Package Weight: 0.200kg
Package Size: 15cm x 10cm x 5cm